

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 560 975 B1**

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
24.01.2001 Bulletin 2001/04

(51) Int Cl.7: **E06B 9/174, E06B 9/262,
E06B 9/24**

(21) Application number: **92922052.3**

(86) International application number:
PCT/NL92/00174

(22) Date of filing: **02.10.1992**

(87) International publication number:
WO 93/07353 (15.04.1993 Gazette 1993/10)

(54) **DOUBLE LAYER SHADE**

Doppellagige Verschattungseinrichtung
STORE A DEUX TABLIERS

(84) Designated Contracting States:
AT BE CH DE ES FR GB IT LI NL SE

(30) Priority: **03.10.1991 US 771148**

(43) Date of publication of application:
22.09.1993 Bulletin 1993/38

(73) Proprietor: **Judkins, Ren**
Pittsburgh, Pennsylvania 15205 (US)

(72) Inventor: **Judkins, Ren**
Pittsburgh, Pennsylvania 15205 (US)

(74) Representative: **Smith, Peter James et al**
Serjeants,
25 The Crescent,
King Street
Leicester LE1 6RX (GB)

(56) References cited:
DE-A- 3 246 075 DE-U- 8 505 818
US-A- 4 724 885 US-A- 4 799 524
US-A- 4 953 610 US-A- 4 974 656

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 560 975 B1

Description

Field of the Invention

[0001] The present invention relates to window shades and particularly a double window shade construction having two independently operable shades in a front to back relationship.

Background of the Invention

[0002] Numerous window shades are presently available. Roller shades usually utilize a spring loaded roller which is mounted at the top of a window frame adjacent the window. A panel of material is wound onto the roller which can be unrolled to cover the window. Insulated shades that are quilted with spun batting or foam are more effective for saving energy, but they are bulky and they tend to wrinkle when they roll because the side nearest the roller must accommodate a smaller diameter than the opposite side. Round floating bottom rails have also been used with multiple layer shades with some success. Overall these shades are limited by the selection of fabrics that won't wrinkle and the cost of inventorying relatively expensive sandwiches. Another problem with insulating shades is their flat look that is not considered as aesthetically pleasing as a full undulating multi-faceted look provided by drapes and pleated shades. Finally, multi-layer or insulated shades are generally opaque or nearly so because of their multiple layer nature. Consequently, they are even more limited in the range of light control than most regular non-louvered window coverings.

[0003] Another type of shade utilizes a pleated panel of material which stacks by folding in an accordion fashion. There may be a single layer of zigzag fabric or a zigzag layer with a tab extending off one side of each pleat. The top of the material is attached to a headrail mounted adjacent the window. A bottom rail is provided at the bottom of the material. A cord extends from the top rail through the material to the bottom rail for raising and lowering the pleated shade and for supporting the weight of the bottom rail which allows the fabric to maintain a fullness or three-dimensional character and to re-fold consistently when stacked. This type of shade is available in a variety of fabrics ranging from translucent to opaque. Because of their resilient nature, pleated shades are difficult to insulate, instead the art has developed honeycomb structures using two or three panels of pleated material. Although these panels can be made of different materials they are rigidly affixed to one another and cannot be moved relative to one another and are, therefore, limited in light control. Although the cells effectively reduce thermal convection, the connections between layers act as bridges for thermal conduction and are inviting burrows for insects. When condensation does occur, the moisture is trapped within the cell and often stains the fabric.

[0004] In United States Patent No. 4,953,610 Phillips et al. disclose a double window shade assembly having two independently operable pleated shades located in a front to back relationship. They prefer the front shade to be made of substantially translucent or light passing material while the back shade is made of substantially opaque or light blocking material. The user of the window shade assembly is able to adjust one or both of the front and back shades to control where outside light is able to pass through the assembly. Sunlight may be blocked by the rear shade, pass through the front shade or pass directly into the room without obstruction from either shade. Because there are two adjacent pleated shades, the product is nearly twice as wide as single panel shade. Accordingly, this shade is not suitable for narrow window frames. The system of the '610 patent also includes a single head rail and a primary bottom rail. One cord passes from the head rail through the front shade to the primary bottom rail. A second cord passes from the headrail through the rear shade to the primary bottom rail. These two cords maintain the front shade a fixed distance from the rear shade. Because of this arrangement it is not possible to lower the rear shade without also lowering the front shade. The side edges of pleated-type shades have a zigzag three-dimensional character and are relatively delicate which makes them hard to positively seal for an air-tight energy-effective fit.

[0005] The art has recognized that convection currents will develop between window panes, between a window pane and a shade or between two window shade panels whenever the distance between them exceeds approximately 1.27cm (0.5"). The currents transport heat across air spaces via gravitationally driven circulation reducing the thermal efficiency of the system. Such currents can be significantly reduced by closing at least portions of the gap between the two panels to a distance less than 1.27cm (0.5").

[0006] Roller shades are difficult to install when compared to a pleated shade because they are only supported at the ends and they must be hung plumb or be adjusted with shims in the roll of the fabric so that they roll evenly on the roller. It is common practice to leave a considerable clearance between the end brackets and the fabric to avoid abrading the edge of the fabric on the brackets. It is important to be able to inspect the roller as the shade is being operated, and to be able to shim the diameter of the tube or to adjust the relative position of at least one end bracket. It is an object of this invention to be able to install a single set of mounting brackets that can be mounted anywhere along the length of the headrail as is the common practice in pleated shades and which support the headrail of the pleated shade and the end brackets of the roller shade.

[0007] Although double panel window shades have been proposed for example in United States Patent Nos. 4,974,656 and 4,724,885, the art has not found a shade which combines both a pleated shade and roller shade in a compact, thermally efficient manner and in which

the roller shade and pleated shade are truly independently operable and easily installed.

Summary of the Invention

[0008] I provide a double layer shade having two independently movable layers, the double layer shade comprising a headrail having a bottom and an interior to receive a roller shade, a panel of pleated material attached to the bottom of the headrail thereby permitting the pleated material to be folded and unfolded, a roller shade of the type having a roller and a rolled panel of shade material positioned within the headrail in a manner to permit the panel of shade material to be unrolled to a position substantially parallel to the pleated material when the pleated material is unfolded wherein the unfolded pleated material and unrolled shade material are sufficiently close to one another so that convection currents will not develop therebetween and a guide attached to the bottom of the headrail which guide is sized and positioned to maintain the shade material at a selected distance from the pleated material. The pleated material has a plurality of sections, each of two adjacent sections meet at a pleat preformed therein and alternate pleats project towards a front and back of the panel. Each of those pleats facing the roller shade are provided with a tab extending along substantially the entire width of the pleated material and projecting towards the roller shade. Each tab has a cord hole therein through which a cord is passed, the cord being attached to the headrail and the panel of pleated material at its bottom.

[0009] I position the roller shade and pleated shade so that the gap between them will be such as to impede thermal convection currents when both are in an extended position and mimic the thermal and visual quantities of honeycombs while eliminating thermal bridges, water traps, insect homes, and the limited light control. This configuration also has all of the advantages of roller shades including the ability to be made from low cost films and laminates and to readily seal along its edges. I also provide an integrated compact hardware system that allows either shade layer to be operated from the room side without disturbing the other layer; that can be installed with one set of easily mounted brackets that can be placed anywhere along the length of the headrail or at the ends; and that minimizes the space required to store the two layers when they are raised off the window opening by utilizing the corners of space around the roller. The roller shade and the pleated shade are independently operable to enable a full range of light control and aesthetic alternatives. In this structure one can have both the roller shade and the pleated shade down or have only the roller shade down or have only the pleated shade down or have either of them in any combination of intermediate positions. To achieve the desired degree of privacy the roller shade is preferably made of a substantially opaque or light blocking material whereas the pleated shade is made of a translucent or sheer mate-

rial.

[0010] I prefer to utilize a pleated shade of the type having tabs extending from the rear of the pleats as is disclosed in my United States Patent No. 4,974,656.

[0011] Additional advantages of the present invention will become readily apparent from the following discussion particularly when taken in conjunction with the accompanying drawings.

Brief Description of the Drawings

[0012] Figure 1 is a perspective view of a window shade assembly of the present invention.

[0013] Figure 2 is a side view of the window shade assembly of Figure 1.

[0014] Figure 3 is an end view of a headrail similar to the headrail of the embodiment of Figure 1 with the end cap removed showing a present preferred headrail interior configuration.

[0015] Figure 4 is a top view of the bracket shown in Figure 3.

[0016] Figure 5 is an end view of a second preferred configuration of a headrail for the window shade assembly of the present invention.

[0017] Figure 6 is a view of a third preferred headrail for the window shade assembly of the present invention.

[0018] Figure 7 is an end view of a third preferred headrail assembly for the widow shade of the present invention.

[0019] Figures 8 is a side view showing an optional configuration of the preferred embodiment of Figure 3.

[0020] Figure 9 is a side view showing another optional configuration for the embodiment of Figure 3.

[0021] Figure 10 is a side view partially in section showing a means for adjusting the roller in the preferred embodiments.

Description of the Preferred Embodiments

[0022] As shown in Figures 1 and 2, I provide a headrail 1 which supports both the pleated shade 8 and a roller shade 12. End caps 2 and 3 are provided at either end of the headrail and a roller shade mechanism is mounted within the headrail. The headrail is attached to a wall or window frame 15 shown in chainline in Figure 3. A wall mount may be made through bracket 11 or end caps 2 or 3. A ceiling or wall mount is made through bracket 11. The roller shade 12 is wound around roller 14 which rides on brackets that are preferably built into the end caps 2 and 3. The pleated shade 8 is mounted to the bottom 18 of the pleated subrail 17. If desired, the front face 4 of the headrail can be extended by leg 32 as shown in Figure 3 to obscure all or a portion of fabric stack. I prefer to provide tabs 9 which extend from the rear pleats of fabric 8. Cord 7 passes through holes in the tabs 9 to bottom rail 6 for the pleated shade. The opposite end of cord 7 extends through the end cap 2 or cord back as shown in Figure 1. This cord is used to

raise and lower the pleated shade.

[0023] Roller shades are one of the least expensive methods for covering a window. The fabric is minimal and the hardware and fabrication are simple and well established. However, the appearance for, at least, the inexpensive roller shade is very plain. I expect, therefore, that the roller shade layer will usually be on the window side with an opaque or semi-opaque material that will afford privacy when lowered along with the pleated front shade. The material may also be impervious to water vapor to act as a vapor barrier, aluminized to act as a heat mirror and water-proof to be easily washed. Again, these characteristics are more efficiently achieved with a roller shade than any other system because of its flat nature.

[0024] In the embodiments of Figures 1, 2, 3, 4, 8, 9 and 10, the extended roller shade 12 is positioned behind the pleated material 8. I prefer to provide a shade guide 19 within the headrail. This will assure that shade 12 when extended will be parallel to pleated shade 8. Guide 19 and the pleated fabric are positioned so as to keep tabs 9 of the pleated shade 8 very close to roller shade 12. I prefer that gap 20 between roller shade 12 and tabs 9 not extend more than 1.27cm (1/2"). Then the tab 9 is that close to the roller shade 12 air flow between cells 22, will be greatly restricted. Accordingly, convection currents will not develop between roller shade 12 and pleated shade 8. Since cords 7 pass through cord holes (not shown) in tabs 9 rather than the center of the sections in material 8, the cords are not visible from the front of the shade providing a pleasing visual appearance. The absence of holes in the sections of material 24 also prevents light and air from passing through such holes and therefore enhances the insulating effect of the shade. This effect may be further enhanced by having a metalized rear layer or coating on pleated shade 8 or roller shade 12 or both.

[0025] I prefer to use a sheer or translucent material for the front layer which is pleated shade 8 in the embodiment of Figure 1 so that light may pass through the window and the pleated shade 8 into the room. Preferably the openness factor will be small enough to prevent glare and fading. I further prefer to make roller shade 12 from opaque or nearly opaque material so as to prevent light from passing through it. Thus, one could obtain privacy by pulling down roller shade 12. The front layer of any shade is always decorative and generally the more expensive layer. In the embodiment of Figure 1, the front layer is the pleated shade. Generally, the front layer is lowered to prevent glare and the back layer is lowered only for room darkening or privacy. Both shades can be raised for a clear view or for cleaning the windows.

[0026] The configuration shown in Figures 1, 2, 3, 5, 8, 9 and 10 provide a narrow headrail suitable for most windows. One could also place the shade roller 14 adjacent the pleated shade as shown in Figures 6 and 7. In these embodiments where like numbered parts are similarly numbered, the headrail is shorter, but has a

greater depth than the headrail of Figures 2 and 3. In the embodiment of Figure 6, I prefer to have the roller adjustable in both vertical and horizontal directions which allows adjustment for larger rolls of fabric required for longer windows or thicker fabric types. For these applications the embodiments shown in Figures 6 and 7 would generally better fit into the available space.

[0027] Figure 4 shows a top view of the bracket shown in Figure 3 and is typical of the style used in most of the embodiments. It consists of individual brackets that can be mounted separately anywhere along the width of the window and then the headrail can be snapped into or out of the brackets easily. Any of the embodiments could also be supported by end mounted brackets particularly the embodiment shown in Figure 9 which has a subrail for the pleated shade that is supported only at the ends. The pleated shade can be fabricated separately. Before he puts on the valance, the installer can see the shade from the front for more intuitive adjustments.

[0028] Figure 5 shows an embodiment that has the roller shade in the front and the pleated shade hung underneath the roller. A valance is snapped over the front which is open for fabrication and easier installation. The cords 7 are wound around a tube 34 supported by blocks 36 with a capstan 37 at the one end than turns the tube when the strap 38 is pulled and unwinds off of the capstan which raises the shade. The shade 8 is held in any raised position by locking the strap 38, the capstan 37, or the tube 34. To reverse the process and lower the shade, gravity is allowed to unwind the lift cords 7 and turn the tube 34 which winds the strap 38 back onto the capstan 37. A stop lead 40 clamped onto the strap 38 sets the length of the pleated shade 8.

[0029] As shown in the embodiment of Figure 5, one could reverse the orientation of the device so that the roller shade 12 when viewed from the room appears in front of the pleated shade 8. To achieve the thermal benefits previously described, I prefer that tabs 9 be facing inwardly toward shade 12. It is advisable to have a means for adjusting the roller position relative to the wall or ceiling as shown in Figure 10.

[0030] The embodiment of Figure 6 also includes a strap 38 for rolling up the window shade. One raises the roller shade by pulling downward on the cord and then locking the cord to a cleat or a cord lock to hold any position. The cord 27 is simply released to allow gravity to pull the shade down and spool the cord on the mandril 29 for another cycle. Stop 40 sets the length of the drop. To roll up the shade one then simply pulls on cord 27. A wing type bracket 28 is also shown. This type of bracket is frequently used in window curtains and is readily available.

[0031] Figure 7 reverses the orientation of the embodiment in Figure 6. The valance 26 also incorporates a shade guide 19 for maintaining the proximity of the two shade layers and for sealing the top edge of the roller shade 12 when side seals are used. A second weather seal 42 can also be used to seal the top perimeter of the

shade 12.

[0032] Figure 8 shows an embodiment similar to the one shown in Figure 3 except that it has a one piece headrail. This is easier to fabricate, but more difficult to adjust the shade during installation. It might be necessary to use screamers 44 which might be little straps of plastic film which vibrate and make a sound (scream) when the edge of the roller shade 8 moves across them. This would signal the installer to adjust the screw shown in Figure 10 which in turn raises or lowers the pins 46 that support the shade roller. This adjustment is needed to accommodate windows that are not plumb. Adjustments for roller diameter and fabric thickness should be made at the time of fabrication inspection by inserting shims in the fabric roll. Each end cap 2 and 3 would have an opening in the front face for access to the adjustment screw 48 which is held by a retainer 52 that is fixed to the end cap 3 and allows the screw to turn freely but not translate. The screw then passes through a threaded pin 54 which passes through the lever 56 and also is guided by the horizontal slot 57. When the screw 48 is turned the threaded pin 54 moves to and fro in the horizontal slot which causes the lever to move the roller pin 46 up or down in the vertical slot 58 adjusting the roller relative to the end cap and thus the window frame. Walls 50 are shown for holding end cap 3 to headrail 1.

[0033] Figure 9 shows an embodiment similar to those in Figures 3, 5 and 8 except that the subrail 17 for the pleated shade is only supported by the end caps 2 and 3. The shade guide 19 is larger to strengthen this subrail and also guides the shade 12 between the back leg and the middle leg 61 of the side seal track 62. The side seal can substantially reduce air and light leakage around the edge of the shade. It also helps the shade to roll up accurately by guiding the shade bottom rail 13 shown in Figure 1. The front leg 63 is optional and hides the edge of the pleated shade 8, reduces light leakage and aids privacy when the roller shade 12 is raised. A brush type weather seal 42 is also shown. Although two screws 64 are shown this is only to illustrate that either one could be used or both.

[0034] Although I have shown certain present preferred embodiments of my double layer shade, it should be distinctly understood that the invention is not limited thereby, but may be variously embodied within the scope of the following claims.

Claims

1. An energy efficient double layer shade having two independently movable layers comprising:

- a) a headrail (1) having a bottom and an interior to receive a roller shade (12);
- b) a panel of pleated material (10) attached to the bottom of the headrail (1) thereby permitting the pleated material (10) to be folded and un-

folded;

c) the roller shade (12) being of the type having a roller (14) and a rolled panel of shade material positioned within the headrail (1) in a manner to permit the panel of shade material to be unrolled to a position substantially parallel to the pleated material (10) when the pleated material is unfolded wherein the unfolded pleated material and the unrolled shade material are sufficiently close to one another so that convection currents will not develop therebetween; and

d) a guide (19,119,219) attached to the bottom of the headrail (1) which guide is sized and positioned to maintain the shade material at a selected distance from the pleated material (10); wherein,

the pleated material (10) has a plurality of sections (24), each of two adjacent sections (24) meeting at a pleat preformed therein, alternate pleats projecting towards a front and back of the panel, those pleats facing the roller shade (12) being provided with a tab (9) extending along substantially the entire width of the pleated material and projecting towards the roller shade (12), each tab (9) having a cord hole therein through which a cord (7) passes, the cord (7) being attached to the headrail (1) and to the panel of pleated material at its bottom (6)

2. The double layer shade of claim 1 wherein the roller shade (12) and the panel of pleated material (10) are positioned to be substantially parallel when both are in an extended position and the tabs (9) of the panel of pleated material are separated from the unrolled shade panel (12) by a distance not more than about 1.27cm (0.5") .
3. The double layer shade of claim 1 wherein the roller (14) is mounted above, in front of or behind the panel of pleated material (10).
4. The double layer shade of claim 1 also comprising an adjustable bracket (56) attached between the headrail (1) and the roller (14) to permit adjustment of the roller (14) relative to the headrail (1) to permit movement of one end of the roller (14) along a vertical plane.
5. The double layer shade of claim 1 wherein the shade material (12) is substantially comprised of a light-blocking material and the pleated material (10) is substantially comprised of light-passing material.
6. The double layer shade of claim 1 also comprising a roller cord (38) attached to the roller (14).
7. The double layer shade of claim 1 also comprising

a pleated shade cord (7) connected to the pleated material (10) for unfolding and folding the pleated material, the cord (7) also passing through the headrail (1).

8. The double layer shade of claim 7 also comprising cord collecting means within the headrail (1) for collecting and releasing at least a portion of the pleated shade cord (7).
9. The double layer shade of claim 1 wherein the headrail (1) has a front face (4) sized and configured so that when both the shade material (12) and the pleated material (10) are in a retracted position both materials (10,12) will be entirely behind the front face (4).
10. The double layer shade of claim 1 also comprising a roller cord (38) attached to the roller shade (12) and a pleated shade cord (7) attached to the panel of pleated material (10) wherein both the roller cord (38) and the pleated shade cord (7) pass through a front (4) of the headrail (1)

Patentansprüche

1. Energieeffiziente doppelschichtige Beschattungseinrichtung mit zwei unabhängig voneinander bewegbaren Schichten, die aufweist:

a) eine Kopfschiene (1) mit einem Boden und einem Innenraum zur Aufnahme eines Rollschirmes (12);

b) eine Platte Bahn aus plissiertem Material (10), die an dem Boden der Kopf schiene (1) befestigt ist, wodurch es dem plissierten Material (10) ermöglicht wird, gefaltet und entfaltet zu werden;

c) wobei der Rollschirm (12) von dem Typ ist, daß er eine Trommel (14) bzw. Rolle und eine Rollenplatte bzw. Rollenbahn aus Beschattungsmaterial aufweist, die innerhalb der Kopfschiene (1) in einer Weise angeordnet sind, daß es der Platte bzw. Bahn aus Beschattungsmaterial ermöglicht ist, in eine Position im wesentlichen parallel zu dem plissierten Material (10) entrollt zu werden, wenn das plissierte Material entfaltet ist, wobei das entfaltete plissierte Material und das entrollte Beschattungsmaterial hinreichend nah aneinander sind, daß sich zwischen ihnen keine Konvektionsströme entwickeln; und

d) eine Führung (19, 119, 219), die an dem Boden der Kopf schiene (1) befestigt ist, die der-

artig dimensioniert und positioniert ist, daß das Beschattungsmaterial bei einem ausgewählten Abstand von dem plissierten Material (10) gehalten wird; wobei

das plissierte Material (10) eine Vielzahl von Abschnitten (24) aufweist, wobei jeweils zwei aneinander angrenzende Abschnitte (24) sich in einer darin vorgeformten Falte treffen, alternierende Falten zu einer Vorderseite und Rückseite der Bahn vorstehen, wobei solche Falten, die dem Rollschirm (12) gegenüberliegen, mit einem Endstück (9) versehen sind, das sich entlang im wesentlichen der gesamten Breite des plissierten Materials erstreckt und in Richtung Rollschirm (12) vorspringt, wobei jedes Endstück (9) ein Schnurloch aufweist, durch welches eine Schnur (7) verläuft, wobei die Schnur (7) mit der Kopfschiene (1) und mit der Platte bzw. Bahn aus plissiertem Material an deren Boden (6) verbunden ist.

2. Doppelschichtige Beschattungseinrichtung nach Anspruch 1, wobei der Rollschirm (12) und die Platte bzw. Bahn aus plissiertem Material (10) derartig positioniert sind, daß sie im wesentlichen parallel verlaufen, wenn beide in einer auseinandergezogenen Position sind und die Endstücke (9) der Platte bzw. Bahn aus plissiertem Material von der nicht gerollten Beschattungsbahn (12) durch einen Abstand nicht mehr als etwa 1,27 cm (0.5") entfernt sind.

3. Doppelschichtige Beschattungseinrichtung nach Anspruch 1, wobei die Trommel (14) oberhalb, vor oder hinter der Platte bzw. Bahn aus plissiertem Material (10) angebracht ist.

4. Doppelschichtige Beschattungseinrichtung nach Anspruch 1, die weiterhin eine einstellbare Klammer (56) aufweist, die zwischen der Kopf schiene (1) und der Trommel (14) angebracht ist, um eine Einstellung der Trommel (14) relativ zu der Kopfschiene (1) zu ermöglichen, um eine Bewegung des einen Endes der Trommel (14) entlang einer vertikalen Ebene zu ermöglichen.

5. Doppelschichtige Beschattungseinrichtung nach Anspruch 1, wobei das Beschattungsmaterial (12) im wesentlichen ein lichtblockierendes Material und das plissierte Material (10) im wesentlichen ein lichtdurchlässiges Material aufweist.

6. Doppelschichtige Beschattungseinrichtung nach Anspruch 1, die weiterhin eine Trommelschnur (38), die an der Trommel (14) befestigt ist, aufweist.

7. Doppelschichtige Beschattungseinrichtung nach Anspruch 1, die weiterhin eine Plissierbeschattungsschnur (7) aufweist, die mit dem plissierten

Material (10) zum Entfalten und Falten des plissierten Materials verbunden ist, wobei die Schnur (7) auch durch die Kopfschiene (1) verläuft.

8. Doppelschichtige Beschattungseinrichtung nach Anspruch 7, die weiterhin aufweist Schnur aufnehmende Mittel innerhalb der Kopfschiene (1) zum Aufnehmen bzw. Einziehen und Freigeben wenigstens eines Teils der Plissierbeschattungsschnur (7).
9. Doppelschichtige Beschattungseinrichtung nach Anspruch 1, wobei die Kopfschiene (1) eine Vorderfläche (4) aufweist, die derartig dimensioniert und ausgebildet ist, daß wenn sowohl das Beschattungsmaterial (12) als auch das plissierte Material (10) in einer zurückgezogenen Position sind, beide Materialien (10, 12) vollständig hinter der Vorderfläche (4) angeordnet sind.
10. Doppelschichtige Beschattungseinrichtung nach Anspruch 1, die weiterhin aufweist eine Trommelschnur (38), die an dem Rolllschirm (12) befestigt ist, und eine Plissierbeschattungsschnur (7), die an der Platte bzw. Bahn aus plissiertem Material (10) befestigt ist, wobei sowohl die Trommelschnur (38) als auch die Plissierbeschattungsschnur (7) durch einen Vorderbereich (4) der Kopfschiene (1) verlaufen.

Revendications

1. Store à double couche à gestion efficace de l'énergie ayant deux couches mobiles indépendamment, comportant :
 - a) un rail de tête (1) ayant un fond et un intérieur pour recevoir un store en rouleau (12) ;
 - b) un panneau de matériau plissé (10) fixé au fond du rail de tête (1), permettant ainsi au matériau plissé (10) d'être replié et déplié ;
 - c) le store en rouleau (12) étant du type ayant un rouleau (14) et un panneau enroulé de matériau de store positionné à l'intérieur du rail de tête (1) de manière à permettre au panneau de matériau de store d'être déroulé jusqu'à une position sensiblement parallèle au matériau plissé (10) lorsque le matériau plissé est déplié, le matériau plissé déplié et le matériau de store déroulé étant suffisamment proches l'un de l'autre pour que des courants de convection ne se développent pas entre eux ; et
 - d) un guide (19, 119, 219) fixé au fond du rail de tête (1), lequel guide est dimensionné et positionné pour maintenir le matériau de store à une distance sélectionnée du matériau plissé (10) ; dans lequel

le matériau plissé (10) a une pluralité de sections (24), chacune de deux sections adjacentes (24) se rencontrant en un pli qui y est préformé, des plis alternés faisant saillie vers l'avant et vers l'arrière du panneau, les plis faisant face au store en rouleau (12) étant munis d'une patte (9) s'étendant le long sensiblement de la largeur totale du matériau plissé et faisant saillie vers le store en rouleau (12), chaque patte (9) ayant un trou de cordelette à travers lequel passe une cordelette (7), la cordelette (7) étant fixée au rail de tête (1) et au panneau de matériau plissé à sa partie inférieure (6).

2. Store à double couche selon la revendication 1, dans lequel le store en rouleau (12) et le panneau de matériau plissé (10) sont positionnés de façon à être sensiblement parallèles lorsqu'ils sont tous deux en position étendue et les pattes (9) du panneau de matériau plissé sont séparées du panneau de store non enroulé (12) d'une distance ne dépassant pas environ 1,27 cm (0,5 pouce).
3. Store à double couche selon la revendication 1, dans lequel le rouleau (14) est monté au-dessus, devant ou derrière le panneau de matériau plissé (10).
4. Store à double couche selon la revendication 1, comportant également un support ajustable (56) fixé entre le rail de tête (1) et le rouleau (14) afin de permettre l'ajustement du rouleau (14) par rapport au rail de tête (1) pour permettre le déplacement d'une extrémité du rouleau (14) selon un plan vertical.
5. Store à double couche selon la revendication 1, dans lequel le matériau de store (12) est sensiblement constitué d'un matériau arrêtant la lumière et le matériau plissé (10) est sensiblement constitué d'un matériau laissant passer la lumière.
6. Store à double couche selon la revendication 1, comportant également une cordelette de rouleau (38) fixée au rouleau (14).
7. Store à double couche selon la revendication 1, comportant également une cordelette de store plissé (7) attachée au matériau plissé (10) pour déplier et replier le matériau plissé, la cordelette (7) passant également dans le rail de tête (1).
8. Store à double couche selon la revendication 7, comportant également des moyens de collecte de cordelette à l'intérieur du rail de tête (1) pour collecter et relâcher au moins une partie de la cordelette de store plissé (7).
9. Store à double couche selon la revendication 1,

dans lequel le rail de tête (1) possède une face avant (4) dimensionnée et configurée de telle façon que, lorsque à la fois le matériau de store (12) et le matériau plissé (10) sont dans une position rétractée, les deux matériaux (10, 12) soient disposés entièrement derrière la face avant (4). 5

10. Store à double couche selon la revendication 1, comportant également une cordelette de rouleau (38) fixée au store en rouleau (12) et une cordelette de store plissé (7) fixée au panneau de matériau plissé (10), la cordelette de rouleau (38) et la cordelette de store plissé (7) passant toutes deux à travers l'avant (4) du rail de tête (1). 10

15

20

25

30


35



40

45

50

55








FIG. 5




FIG. 6





FIG. 7



BEST AVAILABLE COPY




FIG. 9




FIG. 10